

# Package ‘INFOSET’

January 20, 2025

**Type** Package

**Title** Computing a New Informative Distribution Set of Asset Returns

**Version** 4.1

**Author** Gloria Polinesi [aut, cre],  
Francesca Mariani [aut],  
Maria Cristina Recchioni [aut]

**Maintainer** Gloria Polinesi <g.polinesi@staff.univpm.it>

**Description** Estimation of the most-left informative set of gross returns  
(i.e., the informative set).

The procedure to compute the informative set adjusts the method  
proposed by

Mariani et al. (2022a) <[doi:10.1007/s11205-020-02440-6](https://doi.org/10.1007/s11205-020-02440-6)>

and

Mariani et al. (2022b) <[doi:10.1007/s10287-022-00422-2](https://doi.org/10.1007/s10287-022-00422-2)>

to gross returns of financial assets.

This is accomplished through an adaptive algorithm  
that identifies sub-groups of gross returns in  
each iteration by approximating their distribution with a  
sequence of two-component log-normal mixtures.

These sub-groups emerge when a significant change  
in the distribution occurs below the median of the  
financial returns, with their boundary termed as  
the “change point” of the mixture.

The process concludes when no further change points are detected.

The outcome encompasses parameters of the leftmost mixture  
distributions and change points of the  
analyzed financial time series.

The functionalities of the INFOSET package include: (i) modelling asset distribution  
detecting the parameters which describe left tail behaviour (infoset function), (ii) clustering,  
(iii) labeling of the financial  
series for predictive and classification purposes through a Left Risk mea-  
sure based on the first change point (LR\_cp function)  
(iv) portfolio construction (ptf\_construction function).

The package also provide a specific function to construct rolling windows of differ-  
ent length size and overlapping time.

**License** GPL (>= 2)  
**Encoding** UTF-8  
**LazyData** true  
**Imports** Matrix, colorspace, dendextend, quadprog, mixtools, stats, graphics  
**Depends** R (>= 2.10)  
**RoxygenNote** 7.3.2  
**Suggests** knitr, rmarkdown, testthat (>= 3.0.0)  
**Config/testthat/edition** 3  
**VignetteBuilder** knitr  
**NeedsCompilation** no  
**Repository** CRAN  
**Date/Publication** 2024-11-23 15:20:12 UTC

## Contents

asset.label	2
create_overlapping_windows	3
g_ret	4
infoset	4
LR_cp	6
plot_LR_cp	7
plot_ptf	7
ptf_construction	8
sample.data	9
sample.data.ts	9
summary_ptf	10
tail_mixture	10

<b>Index</b>	<b>11</b>
--------------	-----------

---

asset.label	<i>Data for clustering and labeling ETFs</i>
-------------	--

---

## Description

Contains asset class of ETFs

## Usage

`asset.label`

## Format

A data frame with 44 observations (rows) on 3 variables (columns)

**id** name of ETF

**label** from 1 to 5 according to the specific asset class

**class** specific asset class (5 categories)

## Source

Created in-house to serve as an example

## Examples

```
data(asset.label)
```

---

```
create_overlapping_windows
```

*Function to create overlapping windows.*

---

## Description

Function to create overlapping windows.

## Usage

```
create_overlapping_windows(data, FT = 1290, ov = 125)
```

## Arguments

**data** vector or data frame

**FT** Window size. By default set to 1290 training days (five years).

**ov** Number of different days for two consecutive time windows.. By default set to 125 training days (six months).

## Value

a list containing the rolling windows

<code>g_ret</code>	<i>Function to compute gross returns.</i>
--------------------	---

**Description**

Calculate gross returns from prices.

**Usage**

```
g_ret(x)
```

**Arguments**

<code>x</code>	data object containing ordered price observations
----------------	---

**Value**

An object of the same class as `x` with the gross returns

<code>infoset</code>	<i>Procedure to find the most-left distribution set.</i>
----------------------	--

**Description**

Estimation of the vector of unknown parameters for the density functions associated with the two mixture components.

**Usage**

```
infoset(y, plot_cp)
```

**Arguments**

<code>y</code>	object of class "g_ret"
<code>plot_cp</code>	option

**Value**

An object of class "infoset" is a list containing the following components for the first two iterations ( $k=2$ ):

**change.points** a vector of change points.

**prior.probability** the a priori probabilities.

**first.type.errors** the cumulative distribution functions associated with the leftmost component of the mixture.

**second.type.errors** the cumulative distribution functions associated with the rightmost component of the mixture.

**mean** the parameters (drift) of the left-hand component of the log-normal mixture.

**sd** the parameters (volatility) of the left-hand component of the log-normal mixture.

## References

Mariani, F., Polinesi, G., Recchioni, M. C. (2022). A tail-revisited Markowitz mean-variance approach and a portfolio network centrality. Computational Management Science, 19(3), 425-455.

Mariani, F., Ciommi, M., Chelli, F. M., Recchioni, M. C. (2020). An iterative approach to stratification: Poverty at regional level in Italy. Social Indicators Research, 1-31.

## Examples

```

gross.ret<-as.data.frame(lapply(sample.data, g_ret))
infoset(gross.ret$ETF_1, plot_cp = "T")

#####
## EXAMPLE 1: Clustering ETFs
#####

gross.ret<-as.data.frame(lapply(sample.data, g_ret))
result<-NULL
for(i in 1:ncol(gross.ret)){
  result[[i]]<-infoset(gross.ret[,i], plot_cp = "F")
}
output<-matrix(unlist(result),12,ncol=ncol(gross.ret)) # output contains the information set
output<-t(output)
rownames(output)<-colnames(gross.ret)
colnames(output)<-c("ch_1","ch_2","priori_1","priori_2","first_1",
                     "first_2","second_1","second_2","mean_1","mean_2","dev_1", "dev_2")
output<- as.data.frame(output)
group_label <- as.factor(asset.label$label)
d <- dist(output, method = 'euclidean')
hc_SIMS <- hclust(d, method = 'complete')
library(dendextend)
library(colorspace)
dend_SIMS <- as.dendrogram(hc_SIMS)
dend_SIMS <- color_branches(dend_SIMS, k = 4, col = c(1:4))
labels_colors(dend_SIMS) <-
  rainbow_hcl(5)[sort_levels_values(as.numeric(group_label)[order.dendrogram(dend_SIMS)])]
labels(dend_SIMS) <- paste(as.character(group_label)[order.dendrogram(dend_SIMS)],
                           '(', labels(dend_SIMS), ')', sep = '')
dend_SIMS <- hang.dendrogram(dend_SIMS, hang_height = 0.001)
dend_SIMS <- assign_values_to_leaves_nodePar(dend_SIMS, 0.5, 'lab.cex')
dev.new()
old_par <- par(no.readonly = TRUE)
on.exit(par(old_par))
par(mar = c(1.8, 1.8, 1.8, 1))
plot(dend_SIMS, main = 'Complete linkage (the labels give the true ETF class)',
```

```

horiz = TRUE, nodePar = list(cex = 0.007))
legend('topleft', legend = c('emerging equity Asia', 'emerging equity America',
                            'corporate bond', 'commodities', 'aggregate bond'),
       fill = c('#BDAB66', '#65BC8C', '#C29DDE', '#E495A5', '#55B8D0'), border = 'white')

```

**LR\_cp***Function to compute Left risk measure.***Description**

Function to compute Left risk measure.

**Usage**

```
LR_cp(data, FT, ov)
```

**Arguments**

<b>data</b>	A (T x N) matrix or data.frame containing the N time series over period T
<b>FT</b>	Window size.
<b>ov</b>	umber of different days for two consecutive time windows.

**Value**

A (N x T) data.frame containing the LR\_cp measure for the N time series over time windows

**Examples**

```

LR <- LR_cp(sample.data, FT= 1290, ov = 125)
df <- as.data.frame(matrix(unlist(LR), nrow = length(LR), ncol = ncol(sample.data)))
colnames(df) <- c(paste("tw", rep(1:16)))
plot(df[,1], pch=19, col=asset.label$label, ylab="LR_cp", xlab="ETFs")

```

---

`plot_LR_cp`

*Plot methods for a LR\_cp object*

---

### Description

Plot methods for a LR\_cp object

### Usage

```
plot_LR_cp(LR_cp_measure, asset_label)
```

### Arguments

`LR_cp_measure` object of class LR\_cp

`asset_label` vector containing asset label

### Value

plot of LR\_cp measures by asset classes

---

`plot_ptf`

*Plot methods for a ptf\_construction object*

---

### Description

Plot methods for a ptf\_construction object

### Usage

```
plot_ptf(ptf.oos.values)
```

### Arguments

`ptf.oos.values` object of class ptf\_construction

### Value

plot oos portfolio values

---

<code>ptf_construction</code>	<i>Function to compute portfolio values</i>
-------------------------------	---

---

## Description

Function to compute portfolio values

## Usage

```
ptf_construction(
  data,
  FT,
  ov,
  LR_cp_measure,
  ptf = c("M", "C_M", "EDC", "C_EDC")
)
```

## Arguments

<code>data</code>	A (T x N) matrix or data.frame containing the N time series over period T
<code>FT</code>	Window size.
<code>ov</code>	Overlap.
<code>LR_cp_measure</code>	object of class <code>LR_cp</code> (only for "C_M" and "C_EDC" asset allocation strategies)
<code>ptf</code>	Type of portfolio to be computed. Asset allocation strategies available are: "M" is the Markowitz portfolio, "C_M" is the combined Markowitz portfolio, "EDC" uses the extreme downside correlation and "C_EDC" is the combined extreme downside correlation portfolio

## Value

An object of class "ptf\_construction" is a list containing the following components for all the time windows considered:

**ptf oos value** a vector of out of sample returns.

**weights** portfolio weights.

---

sample.data	<i>Data for infoest function</i>
-------------	----------------------------------

---

**Description**

Contains daily prices of ETFs

**Usage**

```
sample.data
```

**Format**

A data frame with 3174 rows and 44 columns

**Source**

Created in-house to serve as an example

**Examples**

```
data(sample.data)
```

---

sample.data.ts	<i>Data with time points for portfolio construction using the LR_cp measure</i>
----------------	---

---

**Description**

Contains daily prices of ETFs

**Usage**

```
sample.data.ts
```

**Format**

A data frame with 3175 rows and 45 columns

**Source**

Created in-house to serve as an example

**Examples**

```
data(sample.data.ts)
```

`summary_ptf`*Plot methods for a ptf\_construction object***Description**

Plot methods for a ptf\_construction object

**Usage**

```
summary_ptf(ptf.oos.values)
```

**Arguments**

`ptf.oos.values` object of class ptf\_construction

**Value**

summary of oos portfolio values

`tail_mixture`*Function to find the most-left distribution set.***Description**

An adaptive clustering algorithm identifies sub-groups of gross returns at each iteration by approximating their distribution with a sequence of two-component log-normal mixtures.

**Usage**

```
tail_mixture(y, shift, n_it, plot)
```

**Arguments**

<code>y</code>	vector or data frame
<code>shift</code>	double
<code>n_it</code>	integer
<code>plot</code>	option

**Value**

data object

# Index

\* **datasets**  
  asset.label, [2](#)  
  sample.data, [9](#)  
  sample.data.ts, [9](#)  
  
  asset.label, [2](#)  
  
  create\_overlapping\_windows, [3](#)  
  
  g\_ret, [4](#)  
  
  infoset, [4](#)  
  
  LR\_cp, [6](#)  
  
  plot\_LR\_cp, [7](#)  
  plot\_ptf, [7](#)  
  ptf\_construction, [8](#)  
  
  sample.data, [9](#)  
  sample.data.ts, [9](#)  
  summary\_ptf, [10](#)  
  
  tail\_mixture, [10](#)