

# Package ‘docuSignr’

October 13, 2022

**Title** Connect to 'DocuSign' API

**Version** 0.0.3

**Description** Connect to the 'DocuSign' Rest API <<https://www.docusign.com/p/RESTAPIGuide/RESTAPIGuide.htm>>, which supports embedded signing, and sending of documents.

**Depends** R (>= 3.2.2)

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Imports** httr, jsonlite, magrittr

**RoxygenNote** 6.0.1

**Suggests** testthat, covr, drat

**URL** <https://github.com/CannaData/docuSignr>

**BugReports** <https://github.com/CannaData/docuSignr/issues>

**NeedsCompilation** no

**Author** Carl Ganz [aut, cre],  
CannaData Solutions [cph]

**Maintainer** Carl Ganz <carl@cannadatasolutions.com>

**Repository** CRAN

**Date/Publication** 2017-10-22 03:09:17 UTC

## R topics documented:

docu_auth . . . . .	2
docu_download . . . . .	2
docu_embedded_sign . . . . .	3
docu_envelope . . . . .	4
docu_envelope_status . . . . .	5
docu_header . . . . .	6
docu_list_envelopes . . . . .	6

docu_login . . . . .	7
docu_templates . . . . .	8
parse_response . . . . .	8

**Index****9**


---

<i>docu_auth</i>	<i>Create XML authentication string</i>
------------------	---

---

**Description**

Create XML authentication string

**Usage**

```
docu_auth(username = Sys.getenv("docuSign_username"),
           password = Sys.getenv("docuSign_password"),
           integrator_key = Sys.getenv("docuSign_integrator_key"))
```

**Arguments**

username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey

---

<i>docu_download</i>	<i>Download Document from DocuSign</i>
----------------------	--

---

**Description**

Download Document from DocuSign

**Usage**

```
docu_download(file, username = Sys.getenv("docuSign_username"),
              password = Sys.getenv("docuSign_password"),
              integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
              envelope_id)
```

**Arguments**

file	a character string naming a file
username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey
base_url	base_url
envelope_id	id of envelope

## Examples

```
## Not run:
login <- docu_login(demo = TRUE)
envelopes <- docu_list_envelopes(base_url = login$baseUrl[1], from_date = "2017/1/1")
envelope_id <- envelopes=envelopes$status == "completed","envelopeId"])[1]
file <- tempfile()
document <- docu_download(file, base_url = login[1, 3],
                           envelope_id = envelope_id)

## End(Not run)
```

docu\_embedded\_sign      *Embedded docuSign*

## Description

Get URL for embedded docuSign

## Usage

```
docu_embedded_sign(username = Sys.getenv("docuSign_username"),
                    password = Sys.getenv("docuSign_password"),
                    integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
                    return_url, envelope_id, signer_name, signer_email, client_user_id,
                    authentication_method = "None")

docu_embedded_send(username = Sys.getenv("docuSign_username"),
                    password = Sys.getenv("docuSign_password"),
                    integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
                    return_url, uri, signer_name, signer_email, client_user_id,
                    authentication_method = "None")
```

## Arguments

username	docuSign username
password	docuSign password
integrator_key	docsign integratorKey
base_url	docuSign baseURL
return_url	URL to return to after signing
envelope_id	ID for envelope returned from docu_envelope
signer_name	Name of person signing document
signer_email	Email of person signing document
client_user_id	ID for signer
authentication_method	Method application uses to authenticate user. Defaults to "None".
uri	uri path

## Examples

```
## Not run:
# assuming env variables are properly set up
login <- docu_login()
template <- docu_templates(base_url = login[1, "baseUrl"])
env <- docu_envelope(username = Sys.getenv("docuSign_username"),
password = Sys.getenv("docuSign_password"),
integrator_key = Sys.getenv("docuSign_integrator_key"),
account_id = login[1, "accountId"], base_url = login[1, "baseUrl"],
template_id = template$templateId,
template_roles = list(name = "Name", email = "email@example.com",
roleName = "Role", clientUserId = "1"),
email_subject = "Subject", email_blurb = "Body"
)
URL <- docu_embed(
base_url = login[1, "baseUrl"], return_url = "www.google.com",
signer_name = "Name", signer_email = "email@example.com",
client_user_id = "1",
envelope_id = env$envelopeId
)
## End(Not run)
```

**docu\_envelope**

*Create document for particular instance to be signed*

## Description

Does envelope stuff

## Usage

```
docu_envelope(username = Sys.getenv("docuSign_username"),
password = Sys.getenv("docuSign_password"),
integrator_key = Sys.getenv("docuSign_integrator_key"), account_id,
status = "sent", base_url, template_id, template_roles, email_subject,
email_blurb)
```

## Arguments

username	docuSign username
password	docuSign password
integrator_key	docsign integratorKey
account_id	docuSign accountId
status	envelope status
base_url	docuSign baseURL
template_id	docuSign templateId

```

template_roles  list of parameters passed to template
email_subject   docuSign emailSubject
email_blurb     docuSign emailBlurb

```

## Examples

```

## Not run:
# assuming env variables are properly set up
login <- docu_login()
template <- docu_templates(base_url = login[1, "baseUrl"])
(env <- docu_envelope(username = Sys.getenv("docuSign_username"),
  password = Sys.getenv("docuSign_password"),
  integrator_key = Sys.getenv("docuSign_integrator_key"),
  account_id = login[1, "accountId"], base_url = login[1, "baseUrl"],
  template_id = template$templateId,
  template_roles = list(name = "Name", email = "email@example.com",
    roleName = "Role", clientUserId = "1"),
  email_subject = "Subject", email_blurb = "Body"
))
## End(Not run)

```

`docu_envelope_status`    *Check status of envelope*

## Description

Check status of envelope

## Usage

```
docu_envelope_status(username = Sys.getenv("docuSign_username"),
  password = Sys.getenv("docuSign_password"),
  integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
  envelope_id)
```

## Arguments

username	docuSign username
password	docuSign password
integrator_key	docsign integratorKey
base_url	base_url
envelope_id	id of envelope

## Examples

```
## Not run:
login <- docu_login(demo = TRUE)
envelopes <- docu_list_envelopes(base_url = login$baseUrl[1], from_date = "2017/1/1")
envelope_id <- envelopes=envelopes$status == "completed","envelopeId"][[1]
status <- docu_envelope_status(base_url = login[1, 3],
                                envelope_id = envelope_id)

## End(Not run)
```

docu\_header

*Create header for docuSign*

## Description

Create header for authentication with docuSign

## Usage

```
docu_header(auth)
```

## Arguments

auth	XML object with authentication info
------	-------------------------------------

docu\_list\_envelopes

*List envelopes since date*

## Description

List envelopes since date

## Usage

```
docu_list_envelopes(username = Sys.getenv("docuSign_username"),
                     password = Sys.getenv("docuSign_password"),
                     integrator_key = Sys.getenv("docuSign_integrator_key"), base_url, from_date)
```

## Arguments

username	docuSign username
password	docuSign password
integrator_key	docsign integratorKey
base_url	base_url
from_date	character indicating begin date of search

## Examples

```
## Not run:  
login <- docu_login(demo = TRUE)  
envelopes <- docu_list_envelopes(base_url = login$baseUrl[1], from_date = "2017/1/1")  
  
## End(Not run)
```

---

docu\_login

*Authenticate DocuSign*

---

## Description

Login to DocuSign and get baseURL and accountId

## Usage

```
docu_login(username = Sys.getenv("docuSign_username"),  
           password = Sys.getenv("docuSign_password"),  
           integrator_key = Sys.getenv("docuSign_integrator_key"), demo = FALSE)
```

## Arguments

username	docuSign username
password	docuSign password
integrator_key	docsign integratorKey
demo	indicate whether to use DocuSign demo server

## Examples

```
## Not run:  
# assuming env variables are properly set up  
(login <- docu_login())  
  
## End(Not run)
```

`docu_templates`      *View templates*

### Description

See all templates associated with account

### Usage

```
docu_templates(username = Sys.getenv("docuSign_username"),
               password = Sys.getenv("docuSign_password"),
               integrator_key = Sys.getenv("docuSign_integrator_key"), base_url)
```

### Arguments

<code>username</code>	docuSign username
<code>password</code>	docuSign password
<code>integrator_key</code>	docsign integratorKey
<code>base_url</code>	docuSign baseURL

### Examples

```
## Not run:
login <- docu_login()
templates <- docu_templates(base_url = login[1, 3])

## End(Not run)
```

`parse_response`      *Process results from POST or GET*

### Description

Process results from POST or GET

### Usage

```
parse_response(response)
```

### Arguments

<code>response</code>	Result of POST or GET
-----------------------	-----------------------

# Index

docu\_auth, [2](#)  
docu\_download, [2](#)  
docu\_embedded\_send  
    (docu\_embedded\_sign), [3](#)  
docu\_embedded\_sign, [3](#)  
docu\_envelope, [4](#)  
docu\_envelope\_status, [5](#)  
docu\_header, [6](#)  
docu\_list\_envelopes, [6](#)  
docu\_login, [7](#)  
docu\_templates, [8](#)  
  
parse\_response, [8](#)